




# CHART

OUTDOOR  
FLOOR RECESSED



**0.6**

LED 5W | 220-240VAC | 50-60Hz  
COB 3-step | stainless steel | glass  
1.6m cable | aluminium powder coated

0.39kg IP67 IK08 0.3°


38° 45 118

CODE  
752163I

LIGHT COLOUR LUMEN | CRI CODE  
3000K 290 | >80 4

**OPTIONAL**

CODE  
ground housing 90012201



**0.9**

LED 8W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

0.70kg IP67 IK08 0.3°


38° 78 135

CODE  
752264I

LIGHT COLOUR LUMEN | CRI CODE  
3000K 470 | >80 4

**OPTIONAL**

CODE  
ground housing 90012202



**1.2**

LED 12W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

1.05kg IP67 IK08 0.3°


38° 110 175

CODE  
752364I

LIGHT COLOUR LUMEN | CRI CODE  
3000K 815 | >80 4

**OPTIONAL**

CODE  
ground housing 90012203



**1.6**

LED 15W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

1.05kg IP67 IK09 0.3°

41° 150 185

CODE  
752464I

LIGHT COLOUR LUMEN | CRI CODE  
3000K 1030 | >80 4

**OPTIONAL**

CODE  
ground housing 90012204