




MAP  
OUTDOOR  
FLOOR RECESSED



**0.6**

LED 5W | 220-240VAC | 50-60Hz  
COB 3-step | stainless steel | glass  
1.6m cable | aluminium powder coated


0.38kg IP67 IK08 0.3° 16  
38° 41 100

CODE  
751163L

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	290	>80	4

**OPTIONAL**

CODE  
ground housing 90012201



**0.9**

LED 8W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated


0.70kg IP67 IK08 0.3° 16  
38° 78 135

CODE  
751264L

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	470	>80	4

**OPTIONAL**

CODE  
ground housing 90012202



**1.2**

LED 12W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated


1.01kg IP67 IK08 0.3° 16  
38° 110 120

CODE  
751364L

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	815	>80	4

**OPTIONAL**

CODE  
ground housing 90012203



**1.6**

LED 15W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

1.01kg IP67 IK09 0.3° 16  
41° 150 185

CODE  
751464L

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	1030	>80	4

**OPTIONAL**

CODE  
ground housing 90012204