




STIPO

OUTDOOR
FLOOR PROJECTOR




1.0

LED 7W | 220-240VAC | 50/60Hz
COB 3-step | aluminium powder coated | 2.0m cable

0.5 kg | IP65 | 135° | 38°

CODE
737157D_
737157Y_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	460	>80	4




2.0

LED 7W | 220-240VAC | 50/60Hz
COB 3-step | aluminium powder coated | 2.0m cable

0.49 kg | IP65 | 135° | 38°

CODE
737267D_
737267Y_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	460	>80	4



3.0

LED 7W | 220-240VAC | 50/60Hz
COB 3-step | aluminium powder coated | 2.0m cable

0.5 kg | IP65 | 135° | 38°

CODE
737357D_
737357Y_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	460	>80	4

ALWAYS USE

pole 200 excl. spike

CODE
910062D0
910062Y0

pole 400 excl. spike

910064D0
910064Y0

pole 600 excl. spike

910066D0
910066Y0


pole 800 excl. spike

910068D0
910068Y0

OPTIONAL

CODE
90013106

ground spike



4.0

LED 7W | 220-240VAC | 50/60Hz
COB 3-step | aluminium powder coated | 2.0m cable

0.49 kg | IP65 | 135° | 38°

CODE
737467D_
737467Y_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	460	>80	4

ALWAYS USE

pole 200 excl. spike

CODE
910062D0
910062Y0

pole 400 excl. spike

910064D0
910064Y0

pole 600 excl. spike

910066D0
910066Y0

pole 800 excl. spike

910068D0
910068Y0

OPTIONAL

CODE
90013106

ground spike