





# ORIS

## OUTDOOR WALL RECESSED



p. 485



### 0.7

LED 1/2W | 350/700mA | 3Vf  
PCB 3-step | excl. power supply  
aluminium powder coated

0.28kg IP65 0.3+D 6

47x182 40 4-40

	CODE
	709161W_
	709161D_
	709161B_

LIGHT COLOUR LUMEN | CRI CODE  
3000K 90/150 | >80 4

### ALWAYS USE


power supply IP66

	CODE
350mA   3W	90213101
700mA   3W	90215101

more power supplies on page 699

### OPTIONAL

	CODE
recessed housing incl. plasterkit	90012039
concrete housing	90012044



### 1.3

LED 2/4W | 350/700mA | 6Vf  
PCB 3-step | excl. power supply  
aluminium powder coated

0.34kg IP65 0.3+D 6

115x117 40 4-40

	CODE
	709261W_
	709261D_
	709261B_

LIGHT COLOUR LUMEN | CRI CODE  
3000K 180/300 | >80 4

### ALWAYS USE


power supply IP66

	CODE
350mA   3W	90213101
700mA   7W	90215301

more power supplies on page 699

### OPTIONAL

	CODE
recessed housing incl. plasterkit	90012041
concrete housing	90012040



### 2.0

LED 2/4W | 350/700mA | 6Vf  
PCB 3-step | excl. power supply  
aluminium powder coated

0.42kg IP65 0.3+D 6

115x185 40 4-40

	CODE
	709361W_
	709361D_
	709361B_

LIGHT COLOUR LUMEN | CRI CODE  
3000K 180/300 | >80 4

### ALWAYS USE

power supply IP66

	CODE
350mA   3W	90213101
700mA   7W	90215301

more power supplies on page 699

### OPTIONAL

	CODE
recessed housing incl. plasterkit	90012043
concrete housing	90012042

