






DEEPER IP44

CEILING RECESSED



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.17kg | IP44 | 36°

95 76-79 4-38

CODE	
152261W	
152261B	

LIGHT COLOUR	LUMEN CRI	CODE
2700K	440/600 >90	3
3000K	500/650 >90	5
1800-2850K 16V	280/370 >95	9



For wireless dimming compatible
with Amazon Echo Plus, Philips Hue
and Homee see page 239.

ALWAYS USE

power supply | 500mA

CODE	
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.11kg | IP44

100 76-79 4-38

CODE	
152210W0	
152210B0	

ALWAYS USE

power supply | 12V

CODE	
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.15kg | IP44

115 76-79 4-38

CODE	
152220W0	
152220B0	

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

CODE	
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701