

1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.23kg IP20 $\pm 0.3^\circ$ $\Delta 36^\circ$

$\angle 35^\circ/35^\circ$ $\downarrow 355^\circ$ $\perp 90$

wire springs $\text{①} 86-89$ $\text{②} 4-23$

	CODE
	112361W_
	112361S_
	112361G_
	112361Q_
	112361B_

blade springs $\text{①} 86-89$ $\text{②} \text{min } 6$

	CODE
	112361W_C
	112361B_C

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/710	>90	3
3000K	570/770	>90	5
4000K	620/830	>90	6
1800-2850K	16V 330/450	>95	9

ALWAYS USE

power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.17kg IP20 $\pm 0.3^\circ$

$\angle 35^\circ/35^\circ$ $\downarrow 355^\circ$ $\perp 90$

wire springs $\text{①} 86-89$ $\text{②} 4-23$

	CODE
	112310W0
	112310S0
	112310G0
	112310Q0
	112310B0

blade springs $\text{①} 86-89$ $\text{②} \text{min } 6$

	CODE
	112310W0C
	112310B0C

ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

DEEP ADJUST

CEILING RECESSED

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.21kg IP20 $\pm 0.3^\circ$

$\angle 35^\circ/35^\circ$ $\downarrow 355^\circ$ $\perp 105$

wire springs $\text{①} 86-89$ $\text{②} 4-23$

	CODE
	112320W0
	112320S0
	112320G0
	112320Q0
	112320B0

blade springs $\text{①} 86-89$ $\text{②} \text{min } 6$


	CODE
	112320W0C
	112320B0C

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible
with Amazon Echo Plus, Philips Hue
and Homee see page 239.