






DEEP ADJUST trimless

CEILING RECESSED



1.0 LED

LED LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.23kg IP20 36°

105-110 35°/35° 355° 95

	CODE
	112861W
	112861G
	112861B

LIGHT COLOUR	LUMEN CRI	CODE
2700K	530/710 >90	3
3000K	570/770 >90	5
4000K	620/830 >90	6
1800-2850K 16V	330/450 >95	9

ALWAYS USE

plasterkit 12.5, 15, 20, 25

	CODE
	90017209

power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.17kg IP20 36°

105-110 35°/35° 355° 95

	CODE
	112810W0
	112810G0
	112810B0

ALWAYS USE

plasterkit 12.5, 15, 20, 25

	CODE
	90017209

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.21kg IP20 36°

105-110 35°/35° 355° 110

	CODE
	112820W0
	112820G0
	112820B0

ALWAYS USE

plasterkit 12.5, 15, 20, 25

	CODE
	90017209

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701

available from summer 2020

Rev. 002/2020-10

WEVER & DUCRÉ 184 — 185