



# DEEP ASYM adjust

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350/500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.25kg IP20 0.3° 87-88 4-25

35°/35° 355° 100 87-88 4-25

| CODE |          |
|------|----------|
|      | 112461W_ |
|      | 112461S_ |
|      | 112461G_ |
|      | 112461B_ |

| LIGHT COLOUR             | LUMEN   | CRI | CODE |
|--------------------------|---------|-----|------|
| 2700K                    | 460/610 | >90 | 3    |
| 3000K                    | 470/670 | >90 | 5    |
| 1800-2850K   16V 290/390 | >95     |     | 9    |

## ALWAYS USE

power supply | 500mA

| CODE     |          |
|----------|----------|
| 10W      | 90214405 |
| 15W dim  | 90224501 |
| 20W DALI | 90244602 |

350mA power supplies on page 694



## 1.0 MR16

QR-CBC51 max. 12W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.19kg IP20 0.3° 87-88 4-25

35°/35° 355° 90 87-88 4-25

| CODE |          |
|------|----------|
|      | 112410W0 |
|      | 112410S0 |
|      | 112410G0 |
|      | 112410B0 |

## ALWAYS USE

power supply | 12V

| CODE    |          |
|---------|----------|
| 10W dim | 90221401 |
| 25W dim | 90221701 |
| 70W dim | 90221904 |

more specs on page 699



## 1.0 PAR16

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.23kg IP20 0.3° 87-88 4-25

35°/35° 355° 115 87-88 4-25

| CODE |          |
|------|----------|
|      | 112420W0 |
|      | 112420S0 |
|      | 112420G0 |
|      | 112420B0 |

## OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

| CODE       |          |
|------------|----------|
| 2700K      | 901228W2 |
| 3000K      | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 701