

1.0 LED

LED 8W | 220-240VAC
COB 3-step | phase-cut dim
aluminium powder coated
round cut out for mounting

0.26kg IP20 $\pm 0.3^\circ$ Δ 36°

\angle 30°/30° \curvearrowright 355° \perp 95

wire springs $\textcircled{1}$ 83-86 \curvearrowright 4-30

	CODE
	130468W_
	130468S_
	130468B_

blade springs $\textcircled{1}$ 83-92 \curvearrowright min 4

	CODE
	130468W_C
	130468S_C
	130468B_C

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	515	>90	3
3000K	535	>90	5

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated
round cut out for mounting

0.11kg IP20 $\pm 0.3^\circ$

\angle 35°/35° \perp 95

wire springs $\textcircled{1}$ 83-86 \curvearrowright 4-30

	CODE
	130410W0
	130410S0
	130410B0

blade springs $\textcircled{1}$ 83-92 \curvearrowright min 4

	CODE
	130410W0C
	130410S0C
	130410B0C

ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated
round cut out for mounting

0.14kg IP20 $\pm 0.3^\circ$

\angle 35°/35° \perp 83

wire springs $\textcircled{1}$ 83-86 \curvearrowright 4-30

	CODE
	130420W0
	130420S0
	130420B0

blade springs $\textcircled{1}$ 83-92 \curvearrowright min 4

	CODE
	130420W0C
	130420S0C
	130420B0C


OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701

NOP
CEILING RECESSED



fits into Kaiser ThermoX® 9320-11