




PLANO IP44

CEILING RECESSED



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.21kg IP44 3+0.3+D 36°

74x78 90 4-30

CODE	
118461W	118461B


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	510/695	>90	3
3000K	550/740	>90	5
1800-2850K	16V 300/390	>95	9

ALWAYS USE

power supply | 500mA

CODE	
10W	90214405
15W dim	90224501
20W DALI	90244602

more power supplies on page 695



1.0 MR16

QR-CBC51 max. 35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.15kg IP44 3+0.3+D

74x78 115 4-30

CODE	
118410W0	118410B0


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	510/695	>90	3
3000K	550/740	>90	5
1800-2850K	16V 300/390	>95	9

ALWAYS USE

power supply | 12V

CODE	
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.19kg IP44 3+0.3+D

74x78 115 4-30

CODE	
118420W0	118420B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	510/695	>90	3
3000K	550/740	>90	5
1800-2850K	16V 300/390	>95	9

ALWAYS USE

PAR16 LED GU10 7W | phase-cut dim

CODE	
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible
with Amazon Echo Plus, Philips Hue
and Homee see page 241.

available from spring 2020

Rev. 001/2020-09