



# RINI IP44

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350/500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.16 kg | IP44 | 0.3m | 36°

76-79 | 60 | 4-25

CODE
154161W_
154161B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480/650	>90	3
3000K	520/700	>90	5
1800-2850K	16V 300/400	>95	9

## ALWAYS USE

power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694



## 1.0 MR16

QR-CBC51 max. 12W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.10 kg | IP44 | 0.3m

76-79 | 70 | 4-25

CODE
154110W0
154110B0

## ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699



## 1.0 PAR16

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.14 kg | IP44 | 0.3m

76-79 | 95 | 4-25


CODE
154120W0
154120B0

## OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



only for LED version