



RONY

CEILING RECESSED



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.34kg IP20 35°/35° 36°

102-104 35°/35° 355° 90

4-25

	CODE
White	110161W_
Black	110161B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/710	>90	3
3000K	570/770	>90	5
1800-2850K 16V	330/450	>95	9

ALWAYS USE

power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694



1.0 MR16

QR-CBC51 max.12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.28kg IP20 35°/35°

102-104 35°/35° 355° 75

4-25

	CODE
White	110110W0
Black	110110B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/710	>90	3
3000K	570/770	>90	5
1800-2850K 16V	330/450	>95	9

ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.32kg IP20 35°/35°

102-104 35°/35° 355° 100

4-25

	CODE
White	110120W0
Black	110120B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/710	>90	3
3000K	570/770	>90	5
1800-2850K 16V	330/450	>95	9

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible
with Amazon Echo Plus,
Philips Hue and Homee see
weverducre.com/smartlighting