




SPINEO

CEILING RECESSED



1.0 LED

LED 8W | 220-240VAC
COB 3-step | phase-cut dim
aluminium powder coated

0.20kg IP20 0.3-1D 36°

28°/28° 355° 75

wire springs 79-83 4-16

	CODE
Wire Springs	160168W_
Blade Springs	160168B_

blade springs 79-83 min 4

	CODE
Wire Springs	160168W_C
Blade Springs	160168B_C

LIGHT COLOUR	LUMEN CRI	CODE
2700K	515 >90	3
3000K	535 >90	5



fits into Kaiser ThermoX® 9320-11



For wireless dimming compatible
with Amazon Echo Plus,
Philips Hue and Homee see
weverducre.com/smartlighting

1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.14kg IP20 0.3-1D

35°/35° 355° 65

wire springs 79-83 4-16

	CODE
Wire Springs	160110W0
Blade Springs	160110B0

blade springs 79-83 min 4

	CODE
Wire Springs	160110WOC
Blade Springs	160110B0C

ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.18kg IP20 0.3-1D

35°/35° 355° 70

wire springs 79-83 4-16

	CODE
Wire Springs	160120W0
Blade Springs	160120B0

blade springs 79-83 min 4

	CODE
Wire Springs	160120WOC
Blade Springs	160120B0C

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701