



ROBY IP44

CEILING SURFACE



1.6

LED 13W | 220-240VAC | 50-60Hz
PCB 3-step low flicker
phase-cut dim | aluminium
powder coated brushed | opal
PMMA cover

1.00kg IP44

CODE	
□	135184W_
■	135184B_


LIGHT COLOUR	LUMEN CRI	CODE
2700K	750 >90	3
3000K	820 >90	5

OPTIONAL

dimmer

CODE	
for switch	90019017
for din rail	90019018

more specs on page 699



2.6

LED 18W | 220-240VAC | 50-60Hz
PCB 3-step low flicker
phase-cut dim | aluminium
powder coated brushed | opal
PMMA cover

1.55kg IP44

CODE	
□	135284W_
■	135284B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	1130 >90	3
3000K	1250 >90	5

OPTIONAL

dimmer

CODE	
for switch	90019017
for din rail	90019018

more specs on page 699



3.5

LED 32W | 220-240VAC | 50-60Hz
PCB 3-step low flicker
phase-cut dim | aluminium
powder coated brushed | opal
PMMA cover

2.45kg IP44

CODE	
□	135384W_
■	135384B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	1680 >90	3
3000K	1800 >90	5

OPTIONAL

dimmer

CODE	
for switch	90019017
for din rail	90019018

more specs on page 699