




# SQUBE on base

CEILING SURFACE



p. 363  
p. 371



## 1.0 LED

LED 6W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
aluminium powder coated

0.43kg IP20 0.3°D 39°

90°

	CODE
Light Grey	144264W
Black	144264B


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	415	>80	2
3000K	430	>80	4
1800-3000K	350	>80	9

## OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 699



## 2.0 LED

LED 12W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
aluminium powder coated

0.44kg IP20 0.3°D 32°

90°

	CODE
Light Grey	144464W
Black	144464B


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	711	>80	2
3000K	790	>80	4
1800-3000K	790	>80	9

## OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 699



## 1.0 PAR16

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.43kg IP20 0.3°D

90°

	CODE
Light Grey	144220W0
Black	144220B0

## OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701