

2.0 | 3.0 LED

LED 6W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
aluminium powder coated
brushed

0.66 | 0.82kg | IP20 | 0.3° | A 36°

2.0

200mm


	CODE
	216164W_
	216164G_
	216164P_
	216164B_

3.0

300mm

	CODE
	216264W_
	216264L_
	216264G_
	216264P_
	216264B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	420 >90	3
3000K	440 >90	5
1800-2850K	360 >95	9



2.0 | 3.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated
brushed

0.59 | 0.72kg | IP20 | 0.3°

2.0

200mm

	CODE
	216120W0
	216120G0
	216120P0
	216120B0

3.0

300mm

	CODE
	216220W0
	216220L0
	216220G0
	216220P0
	216220B0

OPTIONAL

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701

ALWAYS USE

A | Single suspension
ceiling base round

	CODE
	90052022
	90052021

B | Invisible ceiling suspension
plasterkit | system - with fixation
and adjustment

	CODE
	90015195

C | Single ceiling base semi recessed

	CODE
	90052026
	90052027

multi suspension options on page 455

