




SQUBE on track

3-PHASE



p. 311




1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated
incl. 3-phase track adapter

0.32kg IP20 0.3°D A 36°

90° 355°

CODE
144720W0
144720B0



2.0 LED

LED 12W | 220-240VAC | 50-60Hz
COB 3-step | phase-cut dim
aluminium powder coated
incl. 3-phase track adapter

0.40kg IP20 0.3°D P A 32°

90° 355°

CODE
144364W_
144364B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	710	>80	2
3000K	790	>80	4
1800-3000K	790	>80	9

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

CODE
2700K 901228W2
3000K 901228W4
1800-2850K 901229S9

more lamps and specs on page 701



3.0 LED

LED 20W | 220-240VAC | 50-60Hz
COB 3-step | phase-cut dim
aluminium powder coated
incl. 3-phase track adapter

0.75kg IP20 0.3°D P A 27°

90° 355°

CODE
144564W_
144564B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1300	>90	3
3000K	1390	>90	5

OPTIONAL

dimmer

CODE
for switch 90019017
for din rail 90019018

more specs on page 699

OPTIONAL

dimmer

CODE
for switch 90019017
for din rail 90019018

more specs on page 699